

2 Zone Microprocessor Based Fire Alarm Control Panel



SIG. Hybrid-1002

FEATURES:-

SYSTEM AS PER IS-2189 : 1999 AND NFPA SPECIFICATIONS,
ALL STATUS DISPLAYED ON LCD DURING STARTUP.
AUTOMATIC ALL ZONE SCANNING AFTER 90 SEC.
ZONE ISOLATION FACILITY VIA INTERNAL SOFTWARE.
INTELLIGENT INBUILT BATTERY COMPARISON CHARGER.
ADVANCE ZONE TESTING FACILITY.
USER FRIENDLY
BUZZER PRODUCES TWO DIFFERENT SOUNDS TO DIFFERENTIATE BETWEEN.
FIRE ALARM CONDITIONS AND FAULT / WARNING CONDITIONS.

TECHNICAL SPECIFICATION:-

CPU	8 BIT ISP PROCESSOR BY BRAND NAME ATMEL
AC SUPPLY	230 VOLT
SYSTEM OPERATING VOLTAGE	24 VOLT .DC
BATTERY	(7.2Ah)12 VOLT X 2 NOS.
FUSE	AC 0.5 A, DC 1.5 A, BATT 3.0 A,
CHARGING VOLTAGE	INTELLIGENT INBUILT COMPARISON 26.6 VOLT DC
E.O.L	4K.7 OHMS.
OUTPUT RELAY CONTACT	FIRE C.NO.NC / FAULT C.NO.NC / COM HOOTER OUT
CABINET DIMENSION	2 - 4 - ZONE / H240XW350XD95 MM (H X W X D)
CABLE ENTRY	20/25 MM 7 NOS. KNOCKOUT LOCATED AT THE TOP & BOTTOM AND REAR OF THE CABINET